




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup> :</b> <b>A47L 9/00, 9/32</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/47101</b> <b>(43) International Publication Date:</b> 17 August 2000 (17.08.00)
<b>(21) International Application Number:</b> PCT/EP00/00232 <b>(22) International Filing Date:</b> 13 January 2000 (13.01.00)  <b>(30) Priority Data:</b> 99200408.5      12 February 1999 (12.02.99)      EP  <b>(71) Applicant:</b> KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).  <b>(72) Inventors:</b> MULDER, Roelf; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). OUDMAN, Benjamin, L.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN WOLFEREN, Paulus, H.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). DORGELO, Jan; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).  <b>(74) Agent:</b> WOLFS, Marc, J., M.; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).		<b>(81) Designated States:</b> CN, JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>

**(54) Title:** VACUUM CLEANER COMPRISING A HOLDER FOR ACCESSORIES



**(57) Abstract**

The invention relates to a vacuum cleaner comprising a housing (1) accommodating a suction unit (7). The vacuum cleaner comprises a suction nozzle (9) which can be coupled to the housing via a suction tube (13) and a suction hose (15). The vacuum cleaner further comprises a handle (17), which is present near a coupling (69) between the suction hose and the suction tube, and a holder (25) for accessories (27, 29), which is detachably coupled to the handle and fits over the handle near a first end (37) and near a second end (39). According to the invention, the holder (25) comprises a bridge portion (41) interconnecting the first end (37) and the second end (39) of the holder, and the holder is detachably coupled to the handle (17) exclusively by means of a coupling member (51) which is present on a portion (53) of the bridge portion which is situated at a distance from the first end and the second end. Thus, the holder can be released from the handle and the holder can be coupled to the handle in a simple manner without much effort. During operation, the user holds the handle and the bridge together, thus preventing the holder from being unintentionally uncoupled from the handle under the influence of, for example, handling forces. In a preferred embodiment, the handle (17) is a tube, while the bridge portion (41) comprises a shell-like portion (41) which is present at least near the first end (37) and near the second end (39), and which partially fits over the handle substantially without clearance. Thus, the holder (25) is secured against torsional movement around the coupling member (51) when it is coupled to the handle.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Vacuum cleaner comprising a holder for accessories.

The invention relates to a vacuum cleaner comprising a housing, which accommodates a suction unit, a suction accessory, which can be coupled to the housing via a suction hose and a suction tube, a handle, which is situated near a coupling between the suction hose and the suction tube, and a holder for further accessories, which is detachably coupled to the handle and connects to said handle near a first end and a second end.

The invention also relates to a holder which can suitably be used in a vacuum cleaner in accordance with the invention.

The invention further relates to a suction hose which can suitably be used in a vacuum cleaner in accordance with the invention, said suction hose comprising the handle of the vacuum cleaner.

The invention additionally relates to a suction tube which can suitably be used in a vacuum cleaner in accordance with the invention, said suction tube comprising the handle of the vacuum cleaner.

A vacuum cleaner of the type mentioned in the opening paragraph is disclosed in EP-B-0 747 000. The handle of the known vacuum cleaner is tubular and forms part of a suction duct of the vacuum cleaner which connects the suction accessory to the suction unit. The holder of the known vacuum cleaner is plate-shaped and extends parallel to the handle in a state wherein the holder is coupled to the handle. A number of further accessories of the vacuum cleaner are detachably coupled to the holder. Since the holder is in the immediate vicinity of the handle, a user of the vacuum cleaner has said accessories close at hand, resulting in a high ease of use. Since the holder connects to the handle only near the two ends of the holder, a relatively large gripping space for the handle is provided between the handle and the holder, so that upon gripping the handle, the user is not hampered by the holder. The known holder comprises, at each of the two ends, a coupling member for coupling the holder to the handle. As a result, a stable coupling of the holder to the handle is achieved.

A drawback of the known vacuum cleaner resides in that uncoupling the holder requires both the first end and the second end of the holder to be uncoupled from the handle,

locking elements by means of which shifting of the holder along the handle in the longitudinal direction is precluded. In this manner, reliably operating locking elements are obtained in a simple manner.

5

These and other aspects of the invention will be apparent from and elucidated with reference to the embodiments described hereinafter.

In the drawings:

Fig. 1 diagrammatically shows a vacuum cleaner in accordance with the  
10 invention,

Fig. 2 shows a handle with a detachably coupled holder of the vacuum cleaner in accordance with Fig. 1,

Fig. 3 is a sectional view taken on the line III-III in Fig. 2,

Fig. 4 is a sectional view taken on the line IV-IV in Fig. 2, and

15 Fig. 5 is a sectional view taken on the line V-V in Fig. 4.

The vacuum cleaner in accordance with the invention, as shown in Fig. 1, is a so-called canister-type vacuum cleaner which comprises a housing 1 which can be moved over a surface 5 to be cleaned by means of a number of wheels 3. The housing 1 accommodates an electrical suction unit 7 which is only diagrammatically shown in Fig. 1. The vacuum cleaner  
20 further comprises a suction accessory 9 which, in the example shown, has a suction nozzle 11. The suction accessory 9 is detachably coupled to the housing 1 via a metal suction tube 13 and a flexible suction hose 15, said suction accessory 9 being pivotably coupled to the suction tube 13, and the suction tube 13 being detachably coupled to a tubular handle 17 secured to the suction hose 15, and the suction hose 15 being detachably coupled to an input 19 of the  
25 housing 1. The input 19 opens into a dust chamber 21 of the housing 1 which is connected to the suction unit 7 via a filter 23. In operation, the suction unit 7 creates a partial vacuum in a suction duct which comprises, in succession, the suction accessory 9, the suction tube 13, the handle 17, the suction hose 15, the input 19 and the dust chamber 21 of the vacuum cleaner. Under the influence of said partial vacuum, dust and dirt particles present on the surface 5 to  
30 be cleaned are sucked via the suction nozzle 11 of the suction accessory 9 and said suction duct towards the dust chamber 21 where they are collected in a disposable dust bag.

As Fig. 1 further shows, the vacuum cleaner is provided with a synthetic resin holder 25 to which a number of further accessories 27, 29 of the vacuum cleaner are detachably attached, such as a number of alternative suction accessories which can be used

instead of the suction accessory 9 to clean, for example, furniture. The holder 25 is detachably coupled to the handle 17 in a manner which will be described in greater detail hereinafter, and the holder is shown in detail in Fig. 2. As shown in Fig. 2, the holder 25 comprises a clamping member 31 which extends substantially parallel to the tubular handle 17. As shown in Fig. 3, the clamping member 31 has a C-shaped cross-section with two elastically deformable cheeks 33, 35 between which the accessories 27, 29 can be clamped. The clamping member 31 of the holder 25 connects to the handle 17 close to a first end 37 and close to a second end 39, said two ends 37 and 39 being interconnected by a bridge 41 forming part of the holder 25. As shown in Fig. 3, the bridge 41 includes a shell-shaped part 43 having a cross-section which is slightly shorter than a half ring. The shell-shaped part 43 extends throughout the holder 25, i.e. throughout the first end 37 of the holder 25, throughout the bridge 41 and throughout the second end 39 of the holder 25. As is also shown in Fig. 3, the shell-shaped part 43 fits partly over the tubular handle 17, viewed throughout the length of the holder 25, both edges 45 and 47 of the shell-shaped part 43 engaging the handle 17 almost without clearance.

Due to the fact that the holder 25 is situated in the immediate vicinity of the handle 17, a user of the vacuum cleaner has the accessories 27, 29 close at hand, so that a great ease of use is provided. Since the clamping member 31 connects with both ends 37 and 39 to the handle 17, and the two ends 37 and 39 are interconnected by the bridge 41, a large gripping space 49 is provided between the clamping member 31 and the bridge 41, in which gripping space the user can place a hand to grip the handle 17. When the user grips the handle 17 via the gripping space 49, he is not hampered by the clamping member 31 with the further accessories 27, 29, so that said construction of the holder 25 provides a great ease of use. As shown in Fig. 2, the tubular handle 17 and the bridge 41 are curved, viewed in a longitudinal direction of the handle 17, so that the gripping space 49 is further increased. By using the bridge 41, a rigid and stable construction of the holder 25 is obtained. Since the bridge 41 comprises said shell-shaped part 43, the handle 17 and the bridge 41 handle nicely. When the user grips the handle 17, he also grips the bridge 41 of the holder 25, so that, during operation, the holder 25 cannot fall from the handle 17 if the holder 25 were to be unintentionally uncoupled from the handle 17, or if forces were to be exerted on the holder 25 during detaching the accessories 27, 29.

In accordance with the invention, the holder 25 is detachably coupled to the handle 17 exclusively by means of a coupling member 51 which is provided on a part 53 of the bridge 41 which is situated at a distance from both ends 37 and 39. In the example shown in Fig. 2, said part 53 of the bridge 41 is closer to the second end 39 than to the first end 37. In

accordance with the invention, said part 53 of the bridge 41 may alternatively be situated centrally between the two ends 37 and 39, or closer to the first end 37 than to the second end 39. As shown in Fig. 2, the coupling member 51 is situated in an enlarged part 55 of the shell-shaped part 43 of the bridge 41, and is shown in section in Fig. 4. As shown in Fig. 4, the coupling member 51 comprises two elastically deformable hooks 57, 59 which are integrated with the shell-shaped part 43 of the bridge 41. In the coupled state, the hooks co-operate with a coupling element 61, which is integrated with the handle 17, and, as shown in Fig. 4, is T-shaped in cross-section. The coupling element 61 extends in the longitudinal direction of the tubular handle 17 and comprises, as shown in Fig. 5, a central part 63 for co-operation with the hooks 57, 59 of the coupling member 51. On either side of the central part 63, the coupling element 61 is provided with parts 65 and 67 which are widened with respect to the central part 63. Since the holder 25 is detachably coupled to the handle 17 exclusively by means of the coupling member 51, the holder 25 can be simply and quickly uncoupled from and coupled to the handle 17. The coupling member 51 and the coupling element 61 are constructed in a simple, robust manner and operate reliably. The holder 25 is uncoupled by simply pulling it from the handle 17, whereby the hooks 57, 59 are elastically deformed. The holder 25 is coupled to the handle 17 by simply snapping it onto the handle 17, which also involves deformation of the hooks 57, 59. Since the coupling element 61 is provided with the parts 65, 67, which are widened with respect to the central part 63, the holder 25 can be coupled to the handle 17 exclusively in a position where the hooks 57, 59 embrace the central part 63. This is a simple way of accurately positioning the holder 25 with respect to the handle 17. In addition, the parts 65, 67, which are widened with respect to the central part 63, also preclude in a simple and reliable manner that, during use, the holder 25 can be moved in the longitudinal direction of the handle 17 as a result of, for example, handling forces. The hooks 57, 59 and the widened parts 65, 67 thus form co-operating locking elements by means of which the holder 25 can be locked with respect to the handle 17, viewed in the longitudinal direction of the handle 17.

It is noted that, at the location of the ends 37 and 39, the holder 25 is not coupled to the handle 17 but only connects to the handle 17, i.e. it fits on the handle 17 substantially without clearance and engages the handle 17 with the two edges 45, 47. Since the cross-section of the shell-shaped part 43 of the bridge is slightly shorter than a half ring, the shell-shaped part 43 is not coupled to the handle 17 near the ends 37 and 39, and the shell-shaped part 43 causes no resistance near the ends 37 and 39 upon uncoupling and removing the holder 25. Since the shell-shaped part 43 extends to a point proximate to the first end 37

and the second end 39, the holder 25 is secured against torsional movements about the coupling member 51 in an efficacious and robust manner. The shell-shaped part 43 thus precludes that the holder 25 can be unintentionally uncoupled from the handle 17 under the influence of such torsional movements, and that the coupling member 51 can be distorted or damaged under the influence of such torsional movements. It is noted that such securing of the holder 25 with respect to the handle 17 is also achieved in an alternative embodiment of the vacuum cleaner in accordance with the invention, wherein the bridge 41 of the holder 25 comprises a shell-shaped part exclusively near the two ends 37 and 39, which shell-shaped part partly fits over the tubular handle 17 substantially without clearance, and wherein the bridge 41 between the two ends 37 and 39 has a different shape or, for example, is recessed in the handle 17.

In the above-described example of the vacuum cleaner in accordance with the invention, the handle 17 is permanently secured to the suction hose 15, and the handle 17 comprises a coupling 69, only diagrammatically shown in Fig. 2, with which the handle 17 can be detachably coupled to the suction tube 13. The suction hose 15, the handle 17 secured to the suction hose 15, and the holder 25 which is detachably coupled to the handle 17 thus constitute a separate part of the vacuum cleaner. It is noted that the invention also includes vacuum cleaners wherein the handle and the holder for further accessories, which is detachably coupled to said handle, are permanently secured to the suction tube, said handle comprising a coupling with which the handle can be detachably coupled to the suction hose. The invention also includes vacuum cleaners wherein the handle and the holder for further accessories, which is detachably coupled to said handle, includes two couplings with which the handle can be detachably coupled to , respectively, the suction hose and the suction tube.

It is further noted that instead of the coupling member 51, another type of coupling member may alternatively be used which is provided on the central part 53 of the bridge 41. For example, instead of the coupling member 51, a central part of the shell-shaped part 43 can be used as the coupling member, in which case the relevant central part of the shell-shaped part 43 has a slightly longer cross-section than a half ring, so that the central part of the shell-shaped part 43 can be made to embrace the tubular handle 17, while being subject to elastic deformation. In addition, instead of the coupling member 51, use can be made, for example, of a coupling member which is provided with a locking slide which is slidably mounted in the shell-shaped part 43 and which co-operates with a locking element provided on the handle 17, said locking slide being slidable against the pretension of a mechanical spring by pushing in at least one operating knob provided on the holder. Other variations may relate

to, for example, a pair of wire springs secured in the shell-shaped part which co-operate with a T-shaped coupling element of the handle, which wire springs can be pressed apart, leading to elastic deformation of the wire springs and to the release of the coupling element, by shifting a slide knob arranged between the two wire springs. Instead of the coupling member 51 and the coupling element 61, in addition, other types of co-operating clamping members can be used which are customary per se, such as a projection for co-operation with a clamping groove. It is further noted that the central part 53 of the bridge 41 in accordance with the invention can also be provided with more than one coupling member for coupling the holder 25 to the handle 17.

In the example of a vacuum cleaner in accordance with the invention, as described hereinabove, the hooks 57, 59 of the coupling member 51 and the coupling element 61 also form co-operating locking elements for precluding movements of the holder 25 along the handle 17 in the longitudinal direction. Finally, it is noted that the handle 17 and the holder 25 in accordance with the invention may also be provided with separate locking elements for precluding such movements.



## CLAIMS:

1. A vacuum cleaner comprising a housing, which accommodates a suction unit, a suction accessory, which can be coupled to the housing via a suction hose and a suction tube, a handle, which is situated near a coupling between the suction hose and the suction tube, and a holder for further accessories, which is detachably coupled to the handle and connects to said  
5 handle near a first end and a second end, characterized in that the holder is provided with a bridge which interconnects both ends of the holder, which holder can be coupled to the handle exclusively by means of a coupling member which is provided on a part of the bridge which is situated at a distance from both ends.
- 10 2. A vacuum cleaner as claimed in claim 1, characterized in that the handle is tubular, while the bridge comprises a shell-shaped part at least near the two ends of the holder, which shell-shaped part partly fits over the tubular handle substantially without clearance.
3. A vacuum cleaner as claimed in claim 2, characterized in that the bridge  
15 comprises a single shell-shaped part which extends from the first end to the second end of the holder and partly fits over the tubular handle substantially without clearance.
4. A vacuum cleaner as claimed in claim 1, 2 or 3, characterized in that the handle and the bridge are curved, viewed in a longitudinal direction of the handle.
- 20 5. A vacuum cleaner as claimed in claim 1, 2, 3 or 4, characterized in that the handle and the bridge are provided with co-operating locking elements by means of which the holder can be locked with respect to the handle, viewed in a longitudinal direction of the handle.
- 25 6. A vacuum cleaner as claimed in claim 1, 2, 3, 4 or 5, characterized in that the coupling member comprises two elastically deformable hooks for co-operation with a coupling element of the handle which, viewed in cross-section, is T-shaped.

7. A vacuum cleaner as claimed in claims 5 and 6, characterized in that the coupling element comprises a central part for co-operation with the hooks of the holder, and the coupling element is provided, on either side of the central part, with parts which are widened with respect to the central part.

5

8. A holder which can suitably be used in a vacuum cleaner as claimed in claim 1, 2, 3, 4, 5 or 6.

9. A suction hose which can suitably be used in a vacuum cleaner as claimed in claim 1, 2, 3, 4, 5, 6 or 7, said suction hose comprising the handle of the vacuum cleaner.

10

10. A suction tube which can suitably be used in a vacuum cleaner as claimed in claim 1, 2, 3, 4, 5, 6 or 7, said suction tube comprising the handle of the vacuum cleaner.




FIG. 1

2/3




FIG. 2

3/3




FIG. 3




FIG. 4




FIG. 5

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/00232

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 A47L9/00 A47L9/32

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A47L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 747 000 A (AKTIEBOLAGET ELECTROLUX) 11 December 1996 (1996-12-11) cited in the application	
A	DE 88 09 157 U (LICENTIA PATENT-VERWALTUNGS-GMBH) 16 November 1989 (1989-11-16)	
A	DE 81 19 955 U (BOSCH-SIEMENS HAUSGERÄTE GMBH) 24 June 1982 (1982-06-24)	
A	US 5 586 360 A (E. G. DIEDERIKS, JR. ET AL.) 24 December 1996 (1996-12-24)	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents :

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&amp;\* document member of the same patent family

Date of the actual completion of the international search

11 May 2000

Date of mailing of the international search report

18/05/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Bourseau, A-M

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 00/00232

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0747000 A	11-12-1996	SE 510059 C CN 1158716 A DE 69601052 D DE 69601052 T SE 9502102 A US 5732438 A	12-04-1999 10-09-1997 14-01-1999 01-07-1999 09-12-1996 31-03-1998
DE 8809157 U	16-11-1989	NONE	
DE 8119955 U	24-06-1982	AT 377575 B NL 8202745 A	10-04-1985 01-02-1983
US 5586360 A	24-12-1996	NONE	